

# SPP-L3000

3-inch Mobile Label Printer



Logistics



Ticketing



Stadium & Arenas



Logistics



Healthcare



Retail

# Compact and Industrial



Compatible with



Made for iPod iPhone iPad



127 mm/sec



Made for iPod iPhone iPad



2.1m

## Premium-Level Performance

- Fully compatible with market-leading programming languages
- Interchangeable programming language without re-setting the mode
- Fast data processing and printing speed up to 5 ips (127 mm/sec)
- Smart Media Detection™
- Anywhere Anyfont™ (Unicode) removes the need to write multiple code pages for each language

## Seamless Mobility

- Simultaneously connects both Bluetooth and WLAN
- Compatible with all major operating systems including Android™, iOS™ and Windows®
- Supports Easy Bluetooth Pairing™ via embedded NFC tag enabling auto pairing
- Smart Wi-Fi setting via mobile devices is available

## Enhanced optimization for field service

- Compact, ergonomic and light-weight (694g)
- 2.1 m / 7 ft. drop rate
- IP54 (Printer only) water and dust proof
- Various accessories and connectivity ports
- Easy to set up the printer status by LCD and control button
- Visual battery status
- Embedded peeler and paper guide

# SPP-L3000

## 3-inch Mobile Label Printer

5x **No.1** RECEIPT  
MOBILE  
PRINTER  
MANUFACTURER



Reported by  
Chunichisha

### Specifications

#### Printer Specifications

##### Print Method

Direct Thermal

##### Print Speed

Up to 5 ips (127 mm/sec - Label, Linerless)  
12.5% pattern

##### Print Resolution

203 dpi

##### Print Width

Up to 72 mm

##### Sensor

Gap  
Black mark  
Paper cover open  
Label presence

#### Media Characteristics

##### Media Type

Label, Linerless (Optional)

##### Media Width

25 ~ 80 mm

##### Media Roll Diameter

Up to 66 mm

##### Media Thickness

0.07 ~ 0.15 mm

##### Media Inner Core

19mm, 12mm

##### Supply Method

Easy Paper Loading

#### Physical Characteristics

##### Dimensions (WxD) (mm)

119.0 x 159.0 x 79.0 mm  
(4.67 x 6.26 x 3.12 inch)

##### Weight

Including battery: 694 g (1.53 lbs.)  
Paper: 257 g (0.57 lbs.)

##### Battery

7.4 V Li-ion, 2,600 mAh,  
Rechargeable Charging time: Up to 2.5 hrs

##### Peeler

Supported

##### Paper guide

Yes (Inner core: 19mm)

##### Display

FSTN LCD (200 x 100 pixels)

#### Performance Characteristics

##### Memory

128 MB SDRAM, 256 MB Flash  
256 MB SDRAM, 512 MB Flash (Optional)

##### Interface

Standard: USB V2.0 HS + Serial

Optional: USB V2.0 HS + Serial + Bluetooth<sup>1</sup> /  
WLAN<sup>2</sup> / Dual Bluetooth<sup>1</sup> + WLAN<sup>2</sup>

Bluetooth<sup>1</sup>: V4.1 Classic & LE

WLAN<sup>2</sup>: 802.11a/b/g/n (Infrastructure, Ad-hoc,  
Wi-Fi Direct, SoftAP) - WEP40/104,  
WPA1/2(PSK, EAP)

\* Easy Bluetooth Pairing™ via NFC

#### Environment Characteristics

##### Temperature

Operating: -15 ~ 50°C (5 ~ 122°F)  
Storage: -30 ~ 70°C (-22 ~ 158°F)

##### Humidity

Operating: 10 ~ 80% RH

##### Water and Dust

IP54

##### Drop Rate

2.1m / 7 ft. drop rate

#### Software

##### Emulation

SLCS, BPL-Z™, BPL-C™

##### Driver / Utility

Windows Driver (Euro Plus/Seagull),  
Virtual COM USB Driver, Utility Program,  
Label Artist Mobile (aOS, iOS), Label Artist-II,  
Bartender UL

##### SDK

iOS SDK, Android SDK, Windows SDK, Linux SDK

#### Fonts / Graphics / Symbologies

##### Fonts

- 10 SLCS Resident Bitmap Fonts
- One SLCS Resident Scalable Font
- 16 BPL-Z™ Resident Bitmap Fonts
- One BPL-Z™ Resident Scalable Font
- 7 BPL-C™ Resident Bitmap Fonts
- 23 Code Page
- Unicode supported  
(UTF-8, UTF-16LE, UTF-16BE)

##### Graphics

Supporting user-defined fonts, graphics,  
formats, layouts, and logos

##### Barcode

1D: Codabar, Code 11, Code 39, Code 93, Code  
128, EAN-13, EAN-8, Industrial 2-of-5,  
Interleaved 2-of-5, Logmars, MSI, Plessey,  
Postnet, GS1 DataBar (RSS-14),  
Standard 2-of-5, UPC/EAN extensions,  
UPC-A, UPC-E, IMB

2D: Aztec, Codablock, Code 49, Data Matrix,  
MaxiCode, MicroPDF417, PDF417,  
QR code, TLC 39

#### Accessories

##### Standard

Belt Strap, Battery Pack, SMPS, Power Cord,  
Paper Disk (Inner core : 12mm)

##### Optional

Shoulder Strap, Single Battery Charger,  
Quad Battery Charger, Serial/USB Cable,  
Fixed Serial/USB Cable, Cleaning Pen



BR-SPP-L3000-EN-SEP18-V1

Copyright © BIXOLON Co., Ltd. All rights reserved. Features and specifications are subject to change without prior notice.

**BIXOLON**®

**BIXOLON Co., Ltd.**  
+82 (0) 31 218 5500  
sales@bixolon.com

**BIXOLON America Inc.**  
+1 858 764 4580  
sales@bixolonusa.com

**BIXOLON Europe GmbH**  
+49 211 68 78 54 0  
sales@bixolon.de

www.Bixolon.com

