

# SD1010S

10.1" TOUCH SCREEN  
MONITOR

Ultra slim and  
sleek design  
Durable and Stylish



1280 x 800 Resolution

## OVERVIEW

Interface: HDMI or USB or USB-C (Alt mode)  
Ultra-thin design is better paired with USB-C  
Capacitive touch as option.  
Black or white chassis as standard.



Ultra- Slim with VESA 75 x 75mm Support



Solid Metal Stand



Tilt Adjustable


# SD-1010S

## 10.1" Touch Screen Monitor


	SD1010S - HDMI	SD1010S - USB	SD1010S - C
Display Size	10.1 inch ( 16:10 )		
Interface	HDMI + DC USB B_type ( Touch )	USB Cable	USB-C(ALT Mode) (Thunderbolt)
Resolution	1280 x 800		
Power Source	DC 12V Adapter (1500mA)	5V USB x 2	Type-C ( Power by USB-C )
Power Consumption	12V / 350 mA	5V / 1200 mA	5V / 1000 mA
Active Area	216.5 (H) x 135.3 (V) mm		
Display Type	TFT-LCD (Wide viewing angle)		
Back Light	LED		
White Luminance	300 cd/m <sup>2</sup>		
Contrast Ratio	1000		
Response Time Tr+Tf	30 msec		
Viewing Angle	178° (Horizontal)/178° (Vertical)		
Operating Temperature	0° C~40° C (Operating)		
Touch (Option)	Touch Function	Projective Capacitive Multi Touch	
	Input Method	Finger	
	Interface	USB	
	Glass Type	Toughened Glass	
	Optical Characteristics	Transparency > 85%	
Physical Dimension	251.2 (W) x 169.8 (L) x 29 (D) mm		
EMC / Safty Standards	FCC, CE		

### I/O TYPES

HDMI (USB-B for touch)



USB



USB-C alt mode

