

POLYTOUCH® FLEX 21.5 SCO

4010081365



Pictures show sample configurations, real product may vary.



DISPLAY

Front	1.2 mm strengthened glass
Coating	Anti-Glare
Surface hardness	7H
Display size	21.5"
Aspect ratio	16:9
Display type	Active matrix TFT LCD with LED backlighting, A+ Grade
Resolution	1920 x 1080 (Full HD)
Colors	16.7 million
Brightness	250 cd/m²
Viewing angle	Horizontal (left/right): 170° /vertical (up/down): 170°
Contrast ratio	1000:1
Backlight lamp life	typ. 30,000 hours to half brightness
Touch technology	PCAP, OGS
Touch driver support	Windows® 10 – Windows® 11

COMPUTER UNIT

Processor	Intel 10 th Gen i3-10100TE Comet Lake 4C/8T 2.3 GHz
Chipset	Q470
Graphics	Intel® UHD graphics 630
Memory	8 GB DDR4
Storage	128 GB SSD
LAN	2 x 1GbE LAN
OS	Windows® 10 (optional)

POWER

Power input	C13, 100 – 240 V AC, 50/60 Hz
-------------	-------------------------------

SYSTEM

Material	Steel, powder coated
Dimensions (WxDxH)	405.9 x 328.9 x 550.3 mm
Weight	19 kg
Mounting	Desk mount, wallmount, pedestal
Colour	RAL 7016; RAL 9010

CONFIGURATION

Scanner/Imager	Datalogic Magellan 1500i
Payment	Prepared for Ingenico Desk 5000
Printer	Epson TM-T88VII
Handheld scanner	Datalogic Gryphon GD4520
Pole light with SEDU controller	

ENVIRONMENTAL CONDITIONS

	Storage	Operating
Temperature	-20°C to +60°C	15°C to 35°C
Humidity	5% to 95% ¹	20% to 90% ¹

¹ non-condensing

CERTIFICATIONS

CE

PACKAGING & INDIVIDUAL WEIGHTS

	Weight net gross	Dimensions	Stack
Complete system	19 kg 25 kg	685 x 385 x 485 mm	max. 3 systemes on top of each other

INTENDED USE/APPLICATION

The device is only to be used as a touch panel in combination with the intended fastening elements (pedestal, wall or table bracket). Other mounting elements must be specified accordingly for the device. The central component of the system consists of a computer with a touch screen. The touchscreen uses Projective Capacitive Technology (PCT) to recognize touch. The system is supplemented by built-in peripheral components. The device can be connected to an IT power distribution system.

DIMENSIONS

Pictures show sample configurations, real product may vary.

