



EM-IS19N

Ultra-Slim Rugged Windows Tablet for Business Use

- New Generation Intel® N150 Processor
- 10.1-inch High-Resolution, High-Brightness Display with Active Stylus Support
- Ultra-Slim 12.7mm Body
- Dual-Band Wi-Fi 6, Optional 4G/5G Connectivity
- IP67 High Protection Rating, 1.8m Drop Resistance
- 2D Barcode Scanning Engine and Front-Facing NFC



| | |
|------------------------|---|
| Durability | <ul style="list-style-type: none">MIL-STD-810H certified6ft drop 26 facesIP67 certified±8kV contact discharge, ±15kV air discharge |
| Operating System | <ul style="list-style-type: none">Windows 11 HomeOptional Windows 11 PRO/IOT |
| Processor | <ul style="list-style-type: none">Intel N150(6MB Cache, up to 3.6GHz, 4 cores, 4 threads, TDP 6W) |
| Graphics | <ul style="list-style-type: none">Intel® Graphics |
| Memory | <ul style="list-style-type: none">8GB LPDDR5 on board |
| Storage | <ul style="list-style-type: none">128GB eMMCOptional 256GB eMMCOptional 512GB UFS |
| Display | <ul style="list-style-type: none">10.1" FHD (1200*1920), 700nits sunlight readable display10-point capacitive touchscreen, support an active stylus |
| Audio | <ul style="list-style-type: none">Integrated microphoneIntegrated 1W speaker x2Class k audio amplifier |
| Camera | <ul style="list-style-type: none">Integrated 5.0 MP front cameraIntegrated 13.0 MP auto-focus rear camera with flash |
| Keyboard & Input | <ul style="list-style-type: none">4 buttons (1 scan key) |
| Network & Connectivity | <ul style="list-style-type: none">Intel® Wi-Fi 6 AX101 (802.11 ax)Bluetooth® V5.2Integrated 4G LTE multi-carrier mobile broadbandOptional 5GIntegrated GPS and Glonass module |

| | |
|--------------------|--|
| Security | <ul style="list-style-type: none">Integrated TPM2.0Integrated fingerprint scannerIntegrated HF-RFID (NFC) reader |
| Data Capture | <ul style="list-style-type: none">Integrated 1D/2D barcode reader |
| I/O Interface | <ul style="list-style-type: none">USB3.2 (Type-C) x2Docking connector (12pin PogoPin) x1Micro SD card x1SIM card x1 |
| Battery & Charging | <ul style="list-style-type: none">33W USB Type-C adapterBattery Li-Ion, 7.74V, 4800mAh, 7.4 hoursRTC 3V/1mA on board |
| Environment | <ul style="list-style-type: none">Operating temperature: -20°C ~ 60°C (-4°F ~ 140°F)Storage temperature: -30°C to 70°C (-22°F~158°F)Humidity: 95% (Non-Condensing) |
| Dimension | <ul style="list-style-type: none">260mm(L) × 174.7mm(W) × 12.7 mm(H) |
| Weight | <ul style="list-style-type: none">930g |
| Accessories | <ul style="list-style-type: none">Standard: adapter, cable(Type-C), rotatable hand strapOptional: docking charger, stylus, leather keyboard |
| Warranty | <ul style="list-style-type: none">one-year limited warranty standard |

1. Please contact your sales representative for feature availability.
2. Battery life data is provided by Emdoor's laboratory. Default test conditions: 300 nits display brightness, 30 cm/70 dB sound level. Actual results may vary depending on test environments and methods.
3. Certified to MIL-STD-810H and IP standards. For specific test items and methods, please refer to the latest official test report.
4. Body dimensions and weight are measured by Emdoor's laboratory. Variations may occur due to measurement methods and manufacturing processes.
5. All product images, specifications, user interface, and features are for reference only and may vary by production batch or other factors. All information is subject to change without prior notice.

ACCESSORIES

Standard



Adapter



Cable (typeC)



Hand Strap

Optional



Docking Charger



Stylus



Leather Keyboard

CONTACT US

Shenzhen Emdoor Information Co., Ltd. (Stock Code: 001314)

Tel: +86-(0)755-2372 2880 Email: marketing.info@emdoor.com

Web: www.emdoorugged.com Address: Emdoor Building, No.8 Guangke 1st Road, Pingshan District, Shenzhen